



ELECTRICAL CHARACTERISTICS : (671-8240 COMPATIBLE)

1. DCR : PIN 1-3 = 55 OHM ± 15%
PIN 4-6 = 65 OHM ± 15%
2. INDUCTANCE (@1KHZ, 1Vrms) : PIN 1-3 = 600mH MIN.
3. Q (@1KHZ, 1Vrms) : PIN 1-3 = 1.1 MIN.
4. IMPEDANCE = 600 OHM ± 15%
5. INSERTION LOSS = 1.3db MAX. (AT 1KHZ, 1V)
6. FREQ. RESP = ± 0.5db (REF. TO 1KHZ) AT 300HZ TO 4KHZ
7. RETURN LOSS = @300HZ = 18db MIN.
@1KHZ = 21db MIN.
@3.4KHZ = 20db MIN.
8. TURN RATIO = 1 : 1 ± 1%
9. POLARITY = PIN 1-4 INPHASE
10. LONGITUDINAL BAL. = 60dB MIN. AT 200HZ TO 4KHZ
11. LEVEL TRACKING (@300HZ, 4Vrms, 4-6 W/H 600 OHM LOAD)
PIN 1-3 = 400 OHM MIN.
12. HI-POT = 3750VAC, 1MINUTE (PRI.-SEC. ONLY)
13. RoHS COMPLIANCE.

				Atech®		TITLE 600 : 600 TRANSFORMER	
				Atech Technology Co., Ltd.		DWG. NO. ATS-007AR	
				TEL: (02)2794-6667 FAX: (02)2794-8004			
				UNITS:	SAFETY		SHEET 1 OF 1
				DATE	P/N:	DRAW	