



ELECTRICAL CHARACTERISTICS : (COMPATIBLE WITH P1200 FOR V.32bis)

1. D.C.R. : PIN 1-3 = 6-4 = 65 OHM ± 5%
2. INDUCTANCE (@200HZ, 10mVrms, PARALLEL) : PIN 1-3 = 4.15H MIN.
3. LEAKAGE INDUCTANCE (@200HZ, 10mVrms, SERIES) : PIN 1-3 = 20mH MAX.
4. RETURN LOSS : (REF. 600 OHM) 300HZ = 21dB MIN.  
1KHZ = 21dB MIN.  
4KHZ = 21dB MIN.
5. INSERTION LOSS : (@1KHZ, 1Vrms) 1-3 = 1.3dB MAX.
6. FREQ. RESPONSE : (REF. 1KHZ) 300 TO 4KHZ = ± 0.5dB
7. TURN RATIO : (@6KHZ, 0.1Vrms) PIN 1-3 : 6-4 = 1 ± 1%
8. DISTORTION : 300HZ, 0dbm : -77dB MAX.
9. HI-POT : (3750VAC, 1mA, 1MIN.) PIN 1-6
10. RoHS COMPLIANT

				<b>Atech</b> <sup>®</sup>		TITLE TRANSFORMER	
				Atech Technology Co., Ltd.		DWG. NO. ATS-079AR	
				TEL:(02)2794-6667 FAX:(02)2794-8004			
				UNITS: M/M	SAFETY		SHEET 1 OF 1
				DATE	P/N:		DRAW