



□ : TUBE

ELECTRICAL CHARACTERISTICS:

- 1.DCR : PIN 1-2 = 3.5Ω MAX.
PIN 2-3 = 2.7Ω MAX.
PIN 4-5 = 50mΩ MAX.
PIN 7-9 = 75mΩ MAX.
- 2.INDUCTANCE (@10KHz, 0.1Vrms):
PIN 3-1 = 1295uH ±10%
- 3.LEAKAGE INDUCTANCE (@100KHz, 0.1Vrms):
PIN 3-1 (PIN 4-5,7-9 SHORT) = 35uH MAX.
- 4.TURN RATIO : (@100KHz, 0.1Vrms):
PIN 3-1 : 4-5 = 10.27 ±2%
PIN 3-1 : 7-9 = 8.69 ±2%
- 5.HI-POT : (@3000VAC, 3mA, 2SEC) PIN 3,4 - PIN 7
- 6.RoHS COMPLIANT

Unit:mm

							TITLE TRANSFORMER	
							DWG. NO. ATS-1380R	
RELEASE					UNITS:		SAFETY	
NO: DESCRIPTION					DATE		P/N:	
DATE					BY		DRAW	
CHK					APPD		SHEET 1 of 1	
REVISIONS							DRAW	