



ELECTRICAL CHARACTERISTICS:

1. D.C.R. PIN 1-3 = 48 ΩHM +/-10% PIN 4-6 = 42 ΩHM +/-10%
2. INDUCTANCE (@250HZ, 0.5Vrms, PARALLEL) 1-3 = 1.5H MIN.
3. IMPEDANCE (@1KHZ, 0dBm, 4-6 W/H 600 ΩHM LOAD)
1-3 = 600 ΩHM +/-10%
4. INSERTION LOSS = 1.0 dB MAX.
(AT 1KHZ, 0dBm, W/H 600 ΩHM LOAD)
5. FREQ. RESP. (@ 300HZ TO 4KHZ, REF. 1KHZ) = +/-0.35dB
6. RETURN LOSS @300HZ = 20dB MIN. @1KHZ = 23dB MIN.
@4KHZ = 23dB MIN.
7. TURN RATIO = 1:1 +/-1%
8. POLARITY = PIN 1-6 INPHASE
9. LONGITUDINAL BAL. = 70dB MIN. (@ 200HZ TO 4KHZ)
10. HI-POT = 1250 VAC, 1mA, 2SEC. (PRI. -SEC.)
11. ROHS COMPLIANCE

						Atech [®] Atech Technology Co., Ltd. TEL:(02)2794-8667 FAX:(02)2794-8004	TITLE 600 : 600 TRANSFORMER	
							DWG. NO. ATS-176R	
RELEASE						UNITS:	SAFETY	
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE	P/N:	SHEET 1 OF 1 DRAW
REVISIONS								