



ELECTRICAL CHARACTERISTICS:

1. D.C.R. : PIN 1-4 = 570 OHM MAX.
PIN 5-8 = 100 OHM MAX.
2. INDUCTANCE (@ 1 KHZ, 1 Vrms) :
PIN 5-8 = 700 mH MIN.
3. IMPEDANCE (@ 1 KHZ, 1 Vrms, PIN 5-8 W/H 1500 OHM LOAD) :
PIN 1-4 = 10K OHM +/- 10%
4. INSERTION LOSS (@ 1KHZ, 1Vrms, PIN 5-8 W/H 1500 OHM LOAD) = 1db MAX.
5. FREQ. RESP.(REF. 1KHZ)
@ 300HZ = +/- 1 dB @ 4KHZ = +/- 0.5 dB
6. TURNS RATIO (@12KHZ,1Vrms) : PIN 1-4 : PIN 5-8 = 2.58 +/- 2%
7. HI-POT (@1000 VAC, 1 mA, 2 sec) PIN 1-5
8. RoHS COMPLIANCE

						Atech [®] Atech Technology Co., Ltd. TEL:(02)2794-6667 FAX:(02)2794-8004	TITLE 10K : 1.5K TRANSFORMER													
							DWG. NO. ATS-251R													
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;">RELEASE</td> <td style="width: 10%;"></td> <td style="width: 10%;"></td> <td style="width: 10%;"></td> <td style="width: 10%;"></td> <td style="width: 10%;"></td> </tr> <tr> <td>NO.</td> <td>DESCRIPTION</td> <td>DATE</td> <td>BY</td> <td>CHK</td> <td>APPD</td> </tr> </table>						RELEASE						NO.	DESCRIPTION	DATE	BY	CHK	APPD	UNITS:	SAFETY	SHEET 1 OF 1
						RELEASE														
NO.	DESCRIPTION	DATE	BY	CHK	APPD															
REVISIONS						DATE	DRAW													