



ELECTRICAL CHARACTERISTICS: (FOR 56Kbps, 2811B COMPATIBLE)

1. D.C.R. : PIN 1-3 = 120 OHM±10%. PIN 6-4 = 120 OHM±10%
2. INDUCTANCE (@200HZ, 1Vrms, PARALLEL) : PIN 1-3 = 16.5H MIN.
3. RETURN LOSS : (REF. 600 OHM)200 TO 3.5KHZ = 25dB MIN.
4. INSERTION LOSS (1KHZ, 0dBm) 2.1 dB TYP.
5. FREQ. RESPONSE: (REF. 1KHZ) 100 TO 4KHZ = +/-0.1dB
6. LONGITUDINAL BALANCE : 200HZ-3.5KHZ 60dB MIN.
7. TURN RATIO : PIN 1-3 : 6-4 = 1+/-1%
8. HI-POT : (@1650VAC, 1mA, 2SEC.) PIN 1-6
9. LEAD FREE

					Atech [®] Atech Technology Co., Ltd. TEL:(02)2794-8887 FAX:(02)2794-8004		TITLE 600 : 360 TRANSFORMER	
							DWG. NO. ATS-273BN	
					UNITS:		SAFETY	
					DATE		SHEET 1 OF 1	
					REVISIONS		DRAW	
NO.	DESCRIPTION	DATE	BY	CHK	APPD			