



ELECTRICAL CHARACTERISTICS : <C1926 COMPATIBLE>

1. DCR : PIN 1-3 = 2-4 = 0.334 OHM ± 10%
PIN 7-9 = 8-10 = 1.52 OHM ± 10%
2. INDUCTANCE : (<@10 KHZ, 1 Vrms, W/H 8-9 SHORT>) 10-7 = 5 mH ± 10%
3. LEAKAGE INDUCTANCE : (<@100 KHZ, 0.1 Vrms, W/H 2-3, 8-9, 10-7 SHORT>)
1-4 = 10 uH MAX.
4. INTERWINDING CAP. : (<@10 KHZ, 0.1 Vrms, W/H 2-3, 8-9 SHORT>)
1-10 = 35 pF MAX.
5. TURN RATIO : (<@15 KHZ, 1 Vrms>) 10-8 : 9-7 = 1 ± 1%
1-3 : 2-4 = 1 ± 1%
10-7 (<8-9 SHORT>) : 1-4 (<2-3 SHORT>) = 2 ± 1%
6. HI-POT : (<@1875 VAC, 1 mA, 2 SEC>) 10-1 (<8-9, 2-3 SHORT>)
7. RoHS COMPLIANCE.

						Atech [®] Atech Technology Co., Ltd. TEL:(02)2794-6667 FAX:(02)2794-8004	TITLE ADSL TRANSFORMER	
							DWG. NO. ATS-512DR	
						UNITS:	SAFETY	
						DATE	P/N:	
REVISIONS						SHEET 1 OF 1 DRAW		
NO.	DESCRIPTION	DATE	BY	CHK	APPD			