

Open Frame A0062FH-150002

Features

- High Efficiency
- High Reliability
- Application: IoT, smart driver



Characteristics

Output Wattage	6W	Load Regulation	15V/±10%; 5V/±5%Vp-p; 3.3V/±5%
Output Voltage	15V; 5V; 3.3V	Ripple & Noise	15V/200mVp-p; 5V/50mVp-p; 3.3V/50mVp-p Max
Output Current	15V/0.25A; 5V/0.1A; 3.3V/0.5A	Efficiency	57%min@115Vac/230Vac
Input Voltage	100Vac/240Vac(90~264Vac min/max)	Surge	±1KV(L-N)±2KV(L-G,N-G),IEC 61000-4-5
Input Current	0.3A(RMS) max	EMI	CISPR 22 class B, FCC class B
Inrush Current	No damage	ESD	Air±8KV, Contact±6KV ,IEC 61000-4-2
Leakage Current(A)	<0.25mA@240Vac	MTBF	100000Hrs min@115V, 100% load, 25°C (Telcordia SR-332, issue 2)
No Load Power Consumption	<0.9W@115Vac/230Vac		

Environmental

Operating Temperature	0°C ~ +40°C
Storage Temperature	-20°C ~ +85°C
Humidity	10%~90%

Safety

Meet CE

Dimension Diagram Unit:mm

