



## Open Frame A0341FH-240010

### Features

- High Efficiency
- High Reliability
- Application: Telecom, Set top box, IT
- High operating temperature(-40°C ~ +90°C)

### Characteristics

Output Wattage	34W	Load Regulation	5.15V/±5%;24V/±5%
Output Voltage	5.1V;24V	Ripple & Noise	5.1V/100mVp-p;24V/240mVp-p max
Output Current	5.1V/2A;24V/1A	Efficiency	75%min@40Vac sine wave,max load
Input Voltage	40Vac(20-60Vac SINE WAVE)	Surge	±1KV(L-L),±2KV(L-G),EN61000-4-5,Criteria B
Input Current	5A(RMS) max@60Vac SINE WAVE	EMI	CISPR 22 class B, FCC class B
Inrush Current	<100A@20Vac SINE WAVE	ESD	Air±8KV, Contact±4KV EN61000-4-2
Leakage Current(A)		MTBF	175000Hrs min., 25°C (Telcordia SR-332, issue 2)
No Load Power Consumption	<1W@60Vac SINE WAVE		

### Environmental

Operating Temperature	-40°C ~ +90°C
Storage Temperature	-40°C ~ +90°C
Humidity	20%~90%

### Safety

Meet CE
---------

### Dimension Diagram Unit:mm

