



#### ELECTRICAL CHARACTERISTICS:

1. D.C.R. PIN 1-3 = 105 OHM +/-10% PIN 4-6 = 105 OHM +/-10%
2. INDUCTANCE (@ 250HZ, 0.5Vrms, PARALLEL) 1-3 = 3 H MIN.
3. IMPEDANCE (@ 1KHZ, 0dBm, 6-4 W/H 400 OHM)  
1-3 = 600 OHM +/-3%
4. INSERTION LOSS = 2.3 dB MAX.  
(@ 1KHZ, 0dBm, W/H 400 OHM LOAD)
5. FREQ. RESP. (@ 300HZ TO 4KHZ, REF. 1KHZ) = +/-0.12dB
6. RETURN LOSS: @300HZ = 28dB MIN. @1KHZ = 35dB MIN.  
@4KHZ = 35dB MIN.
- 7 TURN RATIO : 1-3:6-4 = 1 +/-1%
8. HI-POT = 1250 VAC, 1mA, 2SEC. (PRI.-SEC.)

					 <b>Atech Technology Co., Ltd.</b> <small>TEL:(02)2794-8887 FAX:(02)2794-8004</small>		TITLE 600: 400 TRANSFORMER	
							DWG. NO. ATC-05-042AR	
					UNITS:		SAFETY	
RELEASE					DATE		SHEET 1 of 1	
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE	DRAW	
REVISIONS								