



PIN#6,8,10 CUT OFF

ELECTRICAL CHARACTERISTICS :

1. DCR : PIN 1-3 = 1.2Ω MAX.  
PIN 4-5 = 200mΩ MAX.  
PIN 7-9 = 70mΩ MAX.
2. INDUCTANCE : (@10KHz, 0.1Vrms) :  
PIN 1-3 = 1000uH ±10%
3. LEAKAGE INDUCTANCE ps (@100KHz, 0.1Vrms) :  
PIN 1-3 (PIN 4-5,7-9 SHORT) = 30uH MAX.
4. TURN RATIO : (@100KHz, 0.1Vrms) :  
PIN 3-1 : 5-4 = 8.22 ±2%  
PIN 3-1 : 7-9 = 5.28 ±2%  
PIN 3-2 : 2-1 = 1 ±2%
5. HI-POT : (@4000VAC, 2mA, 2SEC) PIN 3.5 - PIN 7
6. RoHS COMPLIANT

UNIT : mm

					<b>AOEM.</b>		TITLE TRANSFORMER	
							DWG. NO. ATS-1408R	
RELEASE					UNITS:	SAFETY		SHEET 1 of 1
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE	P/N:	DRAW
REVISIONS								