



PIN 7,9 CUT OFF

ELECTRICAL CHARACTERISTICS :

1. DCR : PIN 1-2 = 45mΩ MAX.
PIN 3-4 = 700mΩ MAX.
PIN 6-8 = 660mΩ MAX.
PIN 8-10 = 65mΩ MAX.
2. INDUCTANCE (@10kHz, 0.1Vrms) :
PIN 3-4 = 606uH ±10%
3. LEAKAGE INDUCTANCE (@100kHz, 0.1Vrms) :
PIN 3-4 (PIN 1-2, 6-8-10 SHORT) = 15uH MAX.
4. TURN RATIO (@100kHz, 0.1Vrms) :
PIN 3-4 : 1-2 = 5.54 ±2%
PIN 3-4 : 6-8 = 1.9 ±2%
PIN 3-4 : 8-10 = 6.77 ±2%
5. HI-POT : PIN 1,3,5 - PIN 6,8 (@3000VAC, 2mA, 2SEC)
6. RoHS COMPLIANTE

UNIT : mm

								TITLE TRANSFORMER	
								DWG. NO. ATS-1530R	
RELEASE						UNITS:		SAFETY	
NO: DESCRIPTION						DATE		P/N:	
DATE						BY		DRAW	
DATE						CHK		SHEET 1 of 1	
DATE						APPD		DRAW	
REVISIONS									