



ELECTRICAL CHARACTERISTICS: (FOR V.90, MEET UL1950)

1. D.C.R. : PIN 1-2 = 155 OHM +/-10% PIN 3-4 = 145 OHM +/-10%
2. INDUCTANCE (@1KHZ, 1Vrms LP) : PIN 1-2 = 3Hy MIN.
3. INSERTION LOSS (@ 1KHZ, 0dBm, PIN 3-4 W/H 287 OHM)  
PIN 1-2 = 3.5 dB MAX.
4. FREQ. RESP.(REF. 1KHZ) : @200HZ-4KHZ = +/-0.3dB
5. RETURN LOSS (REF. 600 OHM) : @ 200HZ - 4KHZ = 20dB MIN.
6. TURNS RATIO : PIN 1-2 : PIN4-3 = 1+/-1%
7. LONGITUDINAL BAL. = 60dB MIN.(@200-4KHZ)
8. T.H.D. (@600HZ,-10dBm) = -82dB MAX.
9. HI-POT (@1650VAC, 1mA, 2SEC.) PRI. - SEC.
10. RoHS COMPLIANC.

					<b>Atech</b> <sup>®</sup>		TITLE 600: 287 TRANSFORMER	
					Atech Technology Co., Ltd.		DWG. NO. ATS-274AR	
					TEL:(02)2794-6667 FAX:(02)2794-8004			
					UNITS:		SAFETY	
					DATE		SHEET 1 OF 1	
					REVISIONS		DRAW	
NO.	DESCRIPTION	DATE	BY	CHK	APPD			