

Adapter A012112-TL1



Features

- Meet DoE Level V
- High Reliability
- Application: Telecom, Set top box, modems, VOIP, IT

Characteristics

Output Wattage	24W	Load Regulation	±5%
Output Voltage	12V	Ripple & Noise	150mVp-p Max
Output Current	2A	Efficiency	78.4%min,DOE Level V
Input Voltage	120Vac(100Vac min)	Surge	±8KV(L-N)±10KV(L-G,N-G),IEC 61000-4-5;JEC202,15KV/72ohm&3KV/2ohm.
Input Current	1A(RMS) max	EMI	CISPR 22 class B, FCC class B
Inrush Current	No damage	ESD	Air±8KV, Contact±6KV ,IEC 61000-4-2
Leakage Current(A)	<0.25mA@240Vac	MTBF	50000Hrs min., 100% load, 25°C (MIL-HDBK-217F)
No Load Power Consumption	<0.3W@115Vac/230Vac		

Note:

AC Cable (option) USA/Europe/UK/Aus/Korea/China/Brazil/Argentina

Environmental

Operating Temperature	0°C ~ +40°C	Safety	Meet CE
Storage Temperature	-25°C ~ +85°C		
Humidity	10%~95%		

Safety

Dimension Diagram Unit:mm

