


## Adapter A0403TD-120033



### Features

- Meet DoE Level VI
- High Reliability
- Application: Telecom, Set top box, modems, IT



### Characteristics

Output Wattage	40W	Load Regulation	±5%
Output Voltage	12V	Ripple & Noise	120mVp-p Max
Output Current	3.34A	Efficiency	87.6%min @ 115Vac/230Vac,DOE Level VI
Input Voltage	115Vac/230Vac(90~264Vac min/max)	Surge	±1KV(L-N),±2KV(L-G),EN61000-4-5
Input Current	1.2A(RMS) max	EMI	CISPR 22 class B, FCC class B
Inrush Current	No damage	ESD	Air±8KV, Contact±4KV ,EN61000-4-2
Leakage Current(A)	<0.75mA@240Vac	MTBF	100000Hrs min. @115Vac/230Vac,100% load, 25°C (MIL-HDBK-217F)
No Load Power Consumption	<0.1W@115Vac/230Vac		

### Environmental

### Safety

Operating Temperature	0°C ~ +40°C	UL/cUL/CB/CE/CCC/BSMI/PSE/RCM/BIS/FCC
Storage Temperature	-20°C ~ +60°C	
Humidity	20% ~ 80%	

### Dimension Diagram Unit:mm

