



ELECTRICAL CHARACTERISTICS :

- 1 IMPEDANCE :
PIN 1-3 : 4-6 = 600 OHM ± 10% ; 600 OHM (AT 1KHZ,W/H 80mADC)
- 2 D.C.R. : PIN 1-3 = 147 OHM ± 15%
PIN 4-6 = 104 OHM ± 15%
- 3 INSERTION LOSS (300HZ TO 3.5KHZ, W/H 80mADC)
AT 300HZ = 4.5 db MAX.
AT 1KHZ = 2.7 db MAX
AT 3.5KHZ = 2.7 db MAX.
- 4 RETURN LOSS (300HZ TO 3.5KHZ, W/H 80mADC)
AT 300HZ = 9.5 db MIN.
AT 1KHZ = 11 db MIN.
AT 3.5KHZ = 11 db MIN.
- 5 HI-PDT = 3750VAC, 60HZ, 1mA, 1 MINUTE (LINE-DEVICE)
- 6 INSULATION RES. = 100 OHM MIN. AT 500 VDC (LINE - DEVICE)
- 7 POLARITY : (PIN 1 & PIN 6 INPHASE)
- 8. LEAD FREE.

| | | | | | | | |
|--|--|--|--|--|--------|----------------------|--------------|
| | | | | Atech [®] | | TITLE TRANSFORMER | |
| | | | | Atech Technology Co. Ltd. TEL:022794-6667 FAX:022794-8004 | | DWG. NO. ATS-003N | |
| | | | | UNITS: | SAFETY | | SHEET 1 OF 1 |
| | | | | DATE | P/N: | | DRAW |