


PIN 5,9,10 CUT OFF

UNIT : mm



ELECTRICAL CHARACTERISTIC:

1. DCR : PIN 1-3 = 5.3 Ω MAX.
PIN 2-4 = 410mΩ MAX.
PIN 7-8 = 165mΩ MAX.
2. INDUCTANCE (@10KHz, 0.1Vrms) :
PIN 3-1 = 1800uH ±10%
3. LEAKAGE INDUCTANCE (@100KHz, 0.1Vrms) :
PIN 3-1 (PIN 4-2, 7-8 SHORT) = 81uH MAX.
4. TURN RATIO (@100KHz, 0.1Vrms)
PIN 3-1 : 4-2 = 7.52 ±2%
PIN 3-1 : 8-7 = 7.18 ±2%
5. HI-POT (@1500VAC, 3mA, 2SEC.) PIN 3,4- PIN 8
6. OPERATING TEMPERATURE : -40°C~+85°C
7. RoHS COMPLIANT

					AOEM.		TITLE POWER TRANSFORMER	
							DWG. NO. ATS-1616R	
					UNITS:		SAFETY	
					DATE		P/N:	
REVISIONS							SHEET 1 of 1	
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DRAW		