



* ROHS COMPLIANT

ELECTRICAL CHARACTERISTICS:

- DCR : PIN 6-8 = 250mΩ MAX
PIN 1.2 - 4.5 = 80mΩ MAX
PIN 9-10 = 450mΩ
- INDUCTANCE : (@100kHz, 0.1Vrms) : PIN 6-8 = 50uH ±10%
- LEAKAGE INDUCTANCE (@100kHz, 0.1Vrms)
PIN 6-8 (PIN 1.2-4.5, PIN 9-10 SHORT) = 1.0uH MAX
- TURN RATIO : (@100kHz, 0.1Vrms)
PIN 6-8 : 10-9 = 2.0 ±2%
PIN 6-8 : 4.5-1.2 = 2.0 ±2%
PIN 6-7 : 7-8 = 1 ±2%
- HI-POT : (@1500VAC, 10mA, 2SEC) : PIN 6.10-PIN4.5
- OPERATING TEMPERATURE : -40°C~+125°C

UNIT : mm

								TITLE TRANSFORMER	
								DWG. NO. ATS-1736R	
RELEASE						UNITS:		SAFETY	
NO:		DESCRIPTION		DATE	BY	CHK	APPD	DATE	P/N:
REVISIONS								SHEET 1 of 1	
								DRAW	