



ELECTRICAL CHARACTERISTICS:

1. D.C.R. : PIN 1-3 = 150 Ω M \pm 12% PIN 6-4 = 150 Ω M \pm 12%
2. INDUCTANCE (@250HZ, 1V_{rms}, PARALLEL) : PIN 1-3 = 18H MIN.
3. RETURN LOSS : (REF. 600 Ω M) 200 TO 4KHZ = 30dB MIN.
4. INSERTION LOSS : (@1KHZ, 0dBm) PIN 1-3 = 3 \pm 0.3 dB
5. FREQ. RESPONSE : (REF. 1KHZ) 200 TO 4KHZ = \pm 0.2 dB
6. LONGITUDINAL BALANCE : 200 HZ - 4KHZ 80 dB MIN.
7. TURN RATIO : (@9KHZ, 1V_{rms}) PIN 1-3 : 6-4 = 1 \pm 1%
8. HI-POT : (@1250VAC, 1mA, 2SEC) PRI-SEC
9. RoHS COMPLIANT

						Atech [®] Atech Technology Co., Ltd. TEL:(02)2794-6667 FAX:(02)2794-8004		TITLE 600 : 301 TRANSFORMER	
								DWG. NO. ATS-354BN	
RELEASE						UNITS:		SAFETY	
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE		SHEET 1 OF 1	
REVISIONS								DRAW	