



## Open Frame A060AD8-120015

### Features

- High Efficiency
- High Reliability
- Application: Telecom, IT

### Characteristics

Output Wattage	65W	Load Regulation	±5%
Output Voltage	12V; 5V;5V WIFI; 3.3V	Ripple & Noise	12V/120mVp-p;5V/150mVp-p;5V WIFI/150mVp-p;3.3V/100
Output Current	12V/1.5A; 5V/3A;5V WIFI/3A; 3.3V/	Efficiency	80%min
Input Voltage	100Vac/240Vac(90~264Vac min/max)	Surge	±1KV(L-N)±2KV(L-G,N-G),IEC 61000-4-5
Input Current	1.6A(RMS) max	EMI	CISPR 22 class B, FCC class B
Inrush Current	No damage	ESD	Air±8KV, Contact±4KV ,IEC 61000-4-2
Leakage Current(A)	<0.25mA@240Vac	MTBF	250000Hrs min.@115Vac, 100% load, 25°C (Telcordia SR-332, issue 2)
No Load Power Consumption	<0.6W@115Vac/230Vac		

### Environmental

Operating Temperature	0°C ~ +50°C
Storage Temperature	-20°C ~ +85°C
Humidity	10%~90%

### Safety

Meet CE
---------

### Dimension Diagram Unit:mm

