



ELECTRICAL CHARACTERISTICS :
(PE-65493, 0559-6200-02 COMPATIBLE)

1. D.C.R. : PRI. = 2.4 OHM \pm 25%
SEC. = 2.4 OHM \pm 25%
2. INDUCTANCE (@10KHZ, 100mVrms) : 1-4 (2-3 SHORT) = 22mH MIN.
5-8 (6-7 SHORT) = 22mH MIN.
3. LEAKAGE INDUCTANCE (@100KHZ, 100mVrms) :
1-4 (2-3, 13-16, 14-15 SHORT) = 5uH MAX.
5-8 (6-7, 9-12, 10-11 SHORT) = 5uH MAX.
4. INTERWINDING CAP. (@100KHZ, 100mVrms) : PRI-SEC = 100pF MAX.
5. TURNS RATIO (@10KHZ, 100mVrms) :
A : B : C : D = 1 : 1 : 1 : 1 \pm 2%
6. HI-POT (2KVAC, 1mA, 2SEC) : PRI. - SEC.

					 Atech Technology Co., Ltd. TEL:022794-6667 FAX:022794-8004	TITLE	ISDN-S TRANSFORMER
B	23.5/14/10.9	10/26/00	PAIR	SUEDY		DWG. NO.	ATPL-008
A	PIN = 3.0 \pm 0.35	04/22/99	PAIR	SUEDY	UNITS:	M/M	
	RELEASE	04/09/98	PAIR	SUEDY	SAFETY		
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE	SHEET 1 OF 1
REVISIONS						04/09/98	DRAW Pair