



ELECTRICAL CHARACTERISTICS : (PE-68862 COMPATIBLE)

1. DCR : PIN 10-12 = 4-6 = 0.7 OHM MAX.
PIN 1-3 = 1.2 OHM MAX.
PIN 7-9 = 0.9 OHM MAX.
2. INDUCTANCE (@100KHZ, 50mV) : PRI. = 1.2mH MIN.
3. LEAKAGE INDUCTANCE (@100KHZ, 50mV) : PRI. (SEC. SHORT) = 0.8 uH MAX.
4. INTERWINDING CAP. (@100KHZ, 50mV) : PRI. - SEC. = 37pF MAX.
5. TURNS RATIO : PIN 12-10 : PIN 1-3 = 1CT : 2CT
PIN 4-6 : PIN 9-7 = 1 : 1.36CT
6. HI-POT (@1500VAC, 1mA, 2SEC) : PRI.-SEC.

						Atech [®] Atech Technology Co., Ltd. TEL:(02)2794-6867 FAX:(02)2794-8004	TITLE T1/E1/ISDN TRANSFORMER
							UNITS: M/M
A	T/R J 15.20	08/07/2002	DOLLY	AL	SUEDY	SAFETY	SHEET 1 OF 1
	RELEASE	12/10/98	PAIR		SUEDY		DATE
REVISIONS						12/10/98	