



SUGGESTED FOOTPRINT

ELELCTRICAL CHARACTERISTICS: (L5024-X028 FUNCTION COMPATIBLE)

1. D.C.R. PIN 1-2 = PIN 3-4 = 2 OHM TYP.
PIN 5-6 = PIN 7-8 = 1 OHM TYP.
2. OCL : (@10KHZ, 0.1Vrms, 6-7 SHORT)
PIN 5-8 = 30mH MIN.
3. TURNS RATIO : 2 : 2 : 1 : 1 +/-5%
4. CW(@10KHZ, 0.1Vrms) PIN 1-3 = 120pF TYP.
5. ISOLATION VOLTAGE : 1500Vrms, 2SEC (PRI-SEC)
500Vrms, 2SEC (1-3, 5-7)

					 Atech [®] Atech Technology Co., Ltd. TEL (02)2704-6667 FAX(02)2704-8004		TITLE ISDN-SO TRANSFORMER	
							DWG. NO. ATPL-044	
RELEASE	01/12/99	PAIR		SUEDY	UNITS: M/M	SAFETY		
NO	DESCRIPTION	DATE	BY	CHK	APPD	DATE	SHEET 1 OF 1	
REVISIONS					01/12/99	DRAW <i>Pair</i>		