



ELECTRICAL CHARACTERISTICS:

- D. C. R. : 1-2 = 3-4 = 0.4 OHM MAX, 5-6 = 7-8 = 0.8 OHM MAX.
- INDUCTANCE : (<@100KHZ, 0.2Vrms)
1-2 = 3-4 = 250uH MIN.
- LEAKAGE : (<@100KHZ, 0.2 Vrms, 5-6, 7-8 SHORT)
1-2 = 3-4 = 0.3uH MIN.
- INTERWINDING CAP. : (<@100KHZ, 0.2Vrms)
1-8 = 4-5 = 15PF MAX.
- INSERTION LOSS (@ 1M-20MHZ) : 0.5dB MAX.
- RETURN LOSS (@1M-20MHZ) : -20dB MIN.
- URNS RATIO : PIN 1-2 : PIN 7-8 = 1 : 1.22
PIN 3-4 : PIN 5-6 = 1 : 1.22
- CROSS TALK (<@1M-20MHZ) : -37dB MIN.
- RISE TIME : 5nSEC, MAX.
- HI-POT : 500VAC, 1MA, 2SEC.

						Atech [®] Atech Technology Co., Ltd. TEL:(02)2794-8887 FAX:(02)2794-8004	TITLE	TOKEN RING TRANSFORMER
A	H=7.1 MAX.	06/16/00	FENG		SUEDY		DWG. NO.	ATPL-079
	RELEASE	11/08/99	PAIR		SUEDY	UNITS:	SAFETY	
NO.	DESCRIPTION	DATE	BY	CHK	APPD	M/M		
REVISIONS						DATE		
						11/08/99	SHEET 1 OF 1	
							DRAW <i>Pair</i>	