



ELECTRICAL CHARACTERISTICS: (PE-68822 COMPATIBLE)

- D. C. R. : 10-12 = 4-6 = 1.7 OHM MAX. 1-3 = 2.0 OHM MAX. 7-9 = 1.7 OHM MAX.
- INDUCTANCE : (<@100KHZ, 50mV>)
PRI. = 1.6mH MIN.
- LEAKAGE INDUCTANCE : (<@100KHZ, 50mV>)
PRI. < SEC. SHORT> = 1.0 uH MAX.
- INTERWINDING CAP. : (<@100KHZ, 50mV>)
PRI. - SEC. = 60pF MAX.
- URNS RATIO : PIN 1-3 : PIN 12-10 = 2CT : 1CT
PIN 4-6 : PIN 9-7 = 1CT : 1.36CT
- HI-POT : (<@1500 VAC, 1mA, 2SEC.> PRI.-SEC.
- OPERATING TEMP ; -40 DEG. C TO +85 DEG. C

						Atech [®]	TITLE T1/E1/ISDN TRANSFORMER	
							Atech Technology Co.. Ltd.	DWG. NO. ATPL-087
A	T/R	08/28/2003	PAIR	AL	SUEDY	UNITS: M/M	SAFETY	
	RELEASE	02/18/00	PAIR		SUEDY	DATE	SHEET 1 OF 1	
NO.	DESCRIPTION	DATE	BY	CHK	APPD	02/18/00	DRAW Pair	
REVISIONS								