


ELECTRICAL CHARACTERISTICS : @25°C (PE-T1064 COMPATIBLE)

1. IC GRADE TRANSFER-MOLDED PACKAGE WITHSTAND 235°C IR REFLOW
2. TX PRIMARY PINS : 1-2 , 6-7 , 11-12 , 16-17
3. RX PRIMARY PINS : 38-36 , 33-31 , 28-26 , 23-21
4. PRI/SEC ISOLATION : 1500Vrms
5. TURNS RATIO : (PRI : SEC) 1:1.14 ±2% (TX)
6. TURNS RATIO : (PRI : SEC) 1:1.14CT ±2% (RX)
7. DCL : 1.2mH MINIMUM @100KHZ 50mV
8. PRI/SEC Cw/w : 35pF MAX @100KHZ 50mV
9. PRI LL : 0.6uH MAX @100KHZ 50mV SEC SHORTED
10. PRI DC RESISTANCE : 0.9 OHMS MAX
11. SEC DC RESISTANCE : 1.3 OHMS MAX
12. CROSS TALK : -65dB TYPICAL
13. CMRR : -50dB MINIMUM @1MHZ



						Atech®		TITLE T1/E1/CEPT TRANSFORMER	
						Atech Technology Co., Ltd.		DWG. NO. ATPL-097	
						TEL:(02)2794-6567 FAX:(02)2794-8004			
RELEASE		07/25/00	FENG	SUEDY		UNITS: M/M	SAFETY		SHEET 1 of 1
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE			DRAW Pair
REVISIONS						07/25/00			