



ELECTRICAL CHARACTERISTICS: (FOR AMD 79C30A S-INTERFACE)

- 1 D. C. R. : PIN 1-2 = 1.1 OHM +/-15% PIN 1-6 = 1.1 OHM +/-15%
PIN 3-5 = 9.9 OHM +/-15%
- 2 D. C. R. UNBALANCE : PIN 1-2 / 1-6 = 1 +/-3%
- 3 INDUCTANCE : (@1KHZ, 0.4Vrms) PIN 3-5 = 145mH +/-30%
- 4 LEAKAGE INDUCTANCE : (@1KHZ, 0.4Vrms, W/H PIN 2-6 SHORT)
PIN 3-5 = 40 uH MAX.
- 5 INTERWIDING CAP. : (@10KHZ, 0.4Vrms) PIN 1-4 = 90 pF MAX.
- 6 TURN RATIO : (@10KHZ, 0.4Vrms) PIN 5-3 : 2-6 = 2 +/-1%
- 7 HI-POT : (@500VAC, 1mA, 1 MINUTE) PRI-SEC, PRI-CORE,
SEC-CORE

						Atech [®]		TITLE TRANSFORMER	
						Atech Technology Co., Ltd.		DWG. NO. ATS-077	
						TEL (02)2704-6867 FAX(02)2704-8004			
RELEASE		PAIR		SUEJD		UNITS: M/M		SAFETY	
NO	DESCRIPTION	DATE	BY	CHK	APPD	DATE		SHEET 1 OF 1	
REVISIONS								DRAW Pair	
						E159603			