



ELECTRICAL CHARACTERISTICS:

(FOR SIEMENS PEB2080, 2081, 2085, 2086, 2186, NS TP3420, MITEL MT8930)

1. D.C.R. : PIN 1-3 = 0.6 OHM ?15% PIN 2-4 = 0.6 OHM ?15%
PIN 5-8 = 3.1 OHM ?15%
2. INDUCTANCE :(@10KHZ, 0.1Vrms) PIN 1-4 = 23mH MIN. (PIN 2-3 SHORT)
- 3 INTERWINDING CAPACITANCE :(@10KHZ, 0.1Vrms,)PIN 1-8 = 40 pF MAX.
(PIN 2-3 SHORT)
4. LEAKAGE :(@100KHZ, 0.1Vrms, W/H 2-3,5-8 SHORT) PIN 1-4 = 25uH MAX.
5. TURN RATIO : PIN 8-5 : 1-3 : 2-4 = 4:1:1
6. HI-POT :(@1500 VAC, 1mA, 2SEC) LINE - DEVICE

E	12.8 MAX.	08/27/99	PAIR		SUEDY	Atech [®] Atech Technology Co.. Ltd. TEL:(02)2794-6667 FAX:(02)2794-8004	TITLE	ISDN S TRANSFORMER
D	PITCH	12/16/96					DWG. NO.	ATS-078
C	INDUCTANCE							
	RELEASE		PAIR		SUEDY	UNITS:	SAFETY	SHEET 1 OF 1
NO	DESCRIPTION	DATE	BY	CHK	APPD	M/M		
REVISIONS						DATE	E159603 CA	DRAW <i>Pair</i>