



ELECTRICAL CHARACTERISTICS :

- DCR : PIN 1-2 = 822mΩ MAX.
PIN 3-4 = 414mΩ MAX.
PIN 5-7 = 343mΩ MAX.
PIN 6-8 = 343mΩ MAX.
- INDUCTANCE (@250KHz, 0.1Vrms,
PIN 3-4 = 155uH ±10%
(@250KHz, 0.1Vrms, 0.65A)
PIN 3-4 = 139.5uH MIN.
- LEAKAGE INDUCTANCE
(@250KHz, 0.1Vrms 1-2-5-6-7-8 SHORT)
PIN 3-4 = 3.25uH MAX.
- TURN RATIO(@250KHz, 0.1Vrms)
PIN 3-4 : 2-1 = 1.499 ±2%
PIN 3-4 : 5-7 = 1.499 ±2%
PIN 3-4 : 6-8 = 1.499 ±2%
- HI-POT (@1500VDC, 1mA, 1SEC) : PIN 3-5 , 3-6
(@500VAC, 1mA, 2SEC) : PIN 1-3
- OUTPUT : 12V, 0.6A
- RoHS COMPLIANCE

							TITLE FLYBACK TRANSFORMER	
							DWG. NO. ATS-1423R	
A	CHANGE DIM.	08/27/2014	SHIRLEY	DICK	DICK	UNITS: M/M	SAFETY	SHEET 1 of 1
	RELEASE	07/16/2014	SHIRLEY	BETTY	BETTY			
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE	P/N:	DRAW
REVISIONS						07/16/14		SHIRLEY