



(PIN#1 : INTERCONNECTION)

ELECTRICAL CHARACTERISTICS: (FOR NS TP3410 "U" INTERFACE)

1. D.C.R. 2-11 = 1.6 OHM+/-10% 5-7 = 12.5 OHM+/-10%(6-8 SHORT)
2. INDUCTANCE (@10KHZ, 0.1Vrms, W/H 100mADC) 2-11 = 12.3mH+/-5%
3. LEAKAGE INDUCTANCE (@ 100KHZ, 0.1 Vrms, 5-6-7-8 SHORT) 2-11 = 65uH MAX.
4. INTERWINDING CAP. (@ 100KHZ, 0.1Vrms, 6-8 SHORT) 2-5 = 250 PF MAX.
5. LONGITUDINAL BAL. (@ 40KHZ, 0.1Vrms) = 55dB MIN.
6. THD. (@500HZ, 2.5Vrms W/H 135 OHM LOAD) = -60 dB MAX.
7. TURN RATIO (@4KHZ, 0.1V) 11-2 : 5-8 : 6-7 = 1 : 0.75 :0.75
8. HI-POT (@2000 VAC, 1 mA, 2 SEC.)

						Atech [®] Atech Technology Co., Ltd. TEL:(02)2794-8867 FAX:(02)2794-8004	TITLE TRANSFORMER	
							DWG. NO. ATS-146	
RELEASE		PAIR		SUEDY		UNITS: M/M	SAFETY	SHEET 1 OF 1
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE		DRAW <i>Pair</i>
REVISIONS								