



ELECTRICAL CHARACTERISTICS:

1. D.C.R : (1-2, 3-4 SHORT) 1-3 = TBD  
12-7(10-11-12, 7-8-9 SHORT) = TBD MAX. 5-6 = TBD
2. INDUCTANCE (@250KHz, 0.7Vrms) : 1-3 = 12.4uH ±10%(1-2, 3-4 SHORT)
3. TURN RATIO (@250KHz,0.7Vrms 1-2, 3-4, 7-8-9, 10-11-12 SHORT)  
10-7 : 5-6 = 1 ±3% , 1-3 : 10-7 = 1.496 ±3%
4. HI-POT (@1500VAC, 1mA, 2SEC. 1-2, 3-4, 7-8-9, 10-11-12 SHORT) 5-1, 5-7
5. OUTPUT : PIN 12-7, 11-8, 10-7 = 12V , 4A
6. OPERATING TEMPERATURE RANGE : -40°C~+125°C
7. RoHS COMPLIANT

								TITLE FLYBACK TRANSFORMER	
								DWG. NO. ATS-1482R	
RELEASE		11/11/2014	SHIRLEY	DICK	DICK	UNITS: M/M	SAFETY		SHEET 1 of 1
NO:	DESCRIPTION	DATE	BY	CHK	APPD	DATE	P/N:	DRAW SHIRLEY	
REVISIONS						11/11/14			