



ELECTRICAL CHARACTERISTICS: (2754H2, 2754J2, 2754K2 COMPATIBLE)

- D.C.R. : 1-11 = 5.5 OHM +/-10% 5-7(6-8 SHORT) = 13 OHM +/-10%
- INDUCTANCE (@ 1KHZ, 0.1Vrms, W/H30mADC)  
5-7 (6-8 SHORT) = 81.5mH +/-5.5%
- LEAKAGE INDUCTANCE (@10KHZ, 0.1Vrms, 5-7, 6-8 SHORT)  
1-11 = 170uH MAX.
- URNS RATIO (@40KHZ, 0.1Vrms, 6-8 SHORT)  
5-7 : 11-1 = 1.5 +/-1%
- LONGITUDINAL BALANCE (@40KHZ) = 75dB TYP.
- HI-PDT (@1500VAC, 1mA, 2SEC) PRI.-SEC.

						<b>Atech</b> <sup>®</sup>		TITLE ISDN-U TRANSFORMER		
						Atech Technology Co., Ltd.		DWG. NO. AT-194		
						TEL:(02)2794-6667 FAX:(02)2794-8004				
RELEASE		PAIR	SLEEDY	UNITS	SAFETY		SHEET 1 OF 1			
NO.	DESCRIPTION	DATE	BY	CHK	APPD	M/M	DRAW			
REVISIONS						DATE		Pair		
						05/04/96				